

PANTUM

The New Era for Printing

Reliability is all that matters.

Sick of filling up the paper tray or changing toners? New Pantum high speed automatic duplex P3500 series offers massive paper input up to 1410 pages. This robust machine delivers efficient and reliable printing experience you require for your business.

P3500 Series
Monochrome Laser Printer



Print **12** basketball courts monthly
1.5 basketball courts all at once



Fast Print Speed



Wi-Fi Connectivity and Mobile Printing



**550 Sheet
Optional Paper Tray x 2**



**Convenient One
Step Installation**



**80000 Page
Monthly Duty Cycle**



PANTUM

WWW.PANTUM.COM

KEY SPECIFICATIONS



P3500 Series Monochrome Laser Printer

Model	P3500DN	P3500DW
Printing		
Technology	Mono laser	
Print speed	33ppm (A4) / 35ppm (Letter)	
First print out time	Less than 8.5 seconds	
Max. monthly volume	80000 pages	
Recommended monthly volume	5000 pages	
Processor speed	600 MHZ	
Memory	256MB (Max : 512MB)	
Resolution(dpi)	1200x1200dpi (Max)	
Printer language	PCL5e, PCL6/XL, PS3, PDF	
Duplex mode	Auto	
Network	Yes	
Wi-Fi	No	Yes
Paper handling		
Paper Input tray	250 pages	
Paper Input tray	60 pages	
Optional tray	Yes (550 pages)	
Paper Output tray	150 pages	
Media sizes	A4, A5, A5L A6, JIS B5, ISO B5, B6, Letter, Legal, Executive, Folio, Oficio, Statement, 16K, Big 16K, 32K, Big 32K, No.10 Env., Monarch Env, DL Env, C5 Env, C6 Env, ZL, Japanese Postcard, custom, Yougata4, Younaga3, Nagagata3, Yougata2	
Media types	Multipurpose tray: Plain, Thick (Tough), Thin, Transparency, Cardstock, Label, Envelope Standard tray: Plain, Thin Optional tray: Plain, Thin	
Media Weight	Multipurpose tray: 60~200 g/m ² ; Standard tray: 60~105 g/m ² ; Optional tray: 60-105g/m ²	
General		
Dimensions (wxdxh)	370x370x286mm (14.6"x14.6"x11.3")	
Display	2 line LCD	
Weight (without toner cartridge)	9.4kg (20.7lb)	
Operating temperature range	Recommended temperature: 10-35°C (10-95°F)	
Operating humidity range	Humidity range: 20% - 80%	
Input voltage	110V Model: AC100~127V(±10%), 50Hz/60Hz(±2Hz); 8A 220V Model: AC220~240V(±10%), 50Hz/60Hz(±2Hz); 4A	
Power consumption	Printing: 495W Ready: 50W Sleep: 2W	
Operating system compatibility	Windows Server 2003 / 2008 / 2012 / XP / Vista / Win 7 / Win 8 / Win 8.1 / Win 10 (32/64 Bit); Mac OS 10.7~10.13; Linux: Ubuntu 12.04/14.04 (32/64 Bit)	
Interface	HI-SPEED USB 2.0; Net: IEEE 802.3 10/100/1000Base-TX;	HI-SPEED USB 2.0; Net: IEEE 802.3 10/100/1000Base-TX; WiFi: IEEE 802.11b/g/n;
Energy efficiency	ENERGY STAR® 2.0 certified	
Consumable		
Toner cartridge ⁽¹⁾	Starter cartridge: 3000 pages Replacement capacity: P*-310 (3000 pages); P*-310H (6000 pages); P*-310X (10000 pages)	
What's in the box		
Printer x 1 / 3,000 Pages Toner Cartridge x 1 / USB Interface Cable x 1 / Power Cord x 1 / CD-ROM x 1 / Quick Setup Guide x 1		

(1) As per ISO/IEC 19752 specification (Individual users will experience different results based on their environment and page coverage)
Copyright © 2018 Pantum International Limited. The information contained herein is subject to change without notice. Pantum shall not be liable for technical or editorial errors or omissions contained herein.